



Current BOLT-10

Advantages Of Current™

High Quality

Manufactured using quality materials and technology. Minimum 3yrs warranty. Intertek & UL certified.

Reliable & Durable

Tested to last 10,000+hrs of operation. Rated for indoor/outdoor use.

Optional Power Supply

Adjustable power options from 40A -80A, allow for faster charging and customizable depending on needs.

OCPP Compliant

Integrated and tested with over 50 OCPP charging networks worldwide.

Load Management

Built-in load management functionality allows installation of more chargers with less power.

Quick Installation

Pre-configured stations for any OCPP Network. Simply mount, connect power supply and test.



Ingress Protection



Impact Resistance

Applications



Residential



Commercial



For all sales inquiries contact:



CurrentEVSE.com



info@currentevse.com



Current BOLT-10

Specifications

Model/PN	Pro		
Application	Commercial		
Voltage (Vac)	208-240Vac		
Frequency (Hz)	50-60Hz		
Amperage	40A - 80A		
Max. Power Output	3.8kW - 19.2kW		
Gross Weight	16.1lbs	19.0lbs - 20.3lbs	22.5lbs
Charging Interface	SAE J1772 Compliant, Type1 Plug		
Charging Cable Length	18 ft. (25 ft.optional)		
Wi-Fi	Yes		
4G	LTE		
RFID	ISO14443A/B		
Display	4.3" LCD screen compliant with CTEP		
Data Protocol	OCPP 1.6j		
Operating Temp.	-22°F to 122°F		
Installation Type	Hardwired		
Web Portal Manag.	Yes		
Console Management	Yes		
Certification	UL2594, UL2231-1/-2		

Mounting Options

Single Pedestal

Double Pedestal
Back to back

Double Pedestal
Back to back W/ Cable Management

Double Pedestal
Side by Side W/ Cable Management

Dimensions



For all sales inquiries contact:

CurrentEVSE.com

info@currentevse.com